Infant Care 1-6.99

Mississippi State Department of Health CHILD CARE SURVEY DATA — PART I

	CHILD CARE SURVEY DATA — PART I
$\mathbf{D}A$	OUNTY Wash. ATE S 11/12199 CILITY OPERATOR NAME Stephan: Heder
FA	CIT TIMES BY LACES
	DRESS/PHONE 334 Fairsies
	Greensile ims 38701
Million Contraction	
Section of the sectio	FAMILY DAY CARE HOME DAY CARE CENTER
I.	A. Amount of usable indoor square feet measured:
COLUMN TWO IS NOT THE OWNER, THE	imum number of allowable children 45
\underline{The}	following indicated items shall be completed for licensure:
II.	Building and Grounds Outdoor Play Area
	 A. Install two (2) remote outward opening doors (minimum 32 inches wide). One near the front and one at the rear. B. Clean: (a) walls (b) floors (c) ceiling. C. Repair walls. D. Paint walls. E. Replace floor. F. Install plug covers in all wall outlets. G. Install an approved play area with a barrier of a minimum height of four (4) feet containing at least seventy (70) square feet per child. H. Clean play area of hazardous or potentially hazardous objects. I. Install barriers at kitchen entrance.
	J. Install barriers at stairways.
	— K. Install handrails at steps.
	L. Install barriers at low windows or full length glass doors.
III.	Kitchen Kitchen
-	A. In the kitchen, install: (a) A three (3) compartment sink. (b) A dishwasher with a sanitizing cycle. B. Install a two (2) compartment sink. C. Install a separate handwashing lavatory. D. Install a hood over the stove vented to the outside air. E. Provide overhead light with a shield. F. Remove laundry equipment from the kitchen.
_	G. Install adequate refrigeration with thermometer provided.
	and the ferringeration with thermometer provided.

C_{L-} _D CARE SURVEY DATA - PART II

IV.	Heating			
	A	. Install proper heating (see page 20 of the "Regulations Governing Licensure of Child Care Facilities").		
		Gas heaters, if used, must meet the following requirements:		
		The flame shall be recessed and enclosed with a guard so designed that clothing or other inflammable material cannot be ignited.		
		Each heater shall be equipped with automatic shut-off valve.		
		Each heater shall be vented to the outside.		
	В.	anapproved gas heaters throughout the hullding (space heaters)		
		Frotect floor furnaces with a barrier.		
		Heating shall be adequate to maintain a temperature between 68 degrees and 72 degrees at child height. Accurate thermometers shall be hung throughout the facility.		
V.	Furniture and Equipment			
	A.	Equipment shall be sturdy and safe and shall not have sharp edges, splinters, protruding nails, etc.		
	—— В.	Paint on toys shall be lead-free and nonpoisonous.		
	C.	Chairs and tables shall be of a size appropriate to the size of the children.		
	D.	Individual hooks or compartments provided for each child.		
VI.	Fire Safety			
	A.	An adequate number of ABC type fire extinguishers provided, hung, tagged, and signed by a competent inspector.		
	—— В.	Each employee should understand procedure for using extinguishers.		
	C.	Post fire evacuation plan.		
VII.	General			
	A.	Additional lighting must be installed.		
		Install a telephone.		
	C.	Individual cots or nap pads (waterproof) must be provided.		
	X D.	Facility in compliance with local fire, building and zoning ordinances.		
	E.	Provide diaper changing area.		
VIII.	Other			
IX.	T A 3 3111			
IA.	In Addition, the Following Requirements Shall be Met:			
	1. The in of a Cl	formation in the section labeled Records and Reports of the Regulations Governing the Licensure nild Care Facility must be kept on file at all times.		
	2. A cert	ificate of inspection and approval by the fire department and the level level and		
	3. Notice	of compliance with local zoning and building ordinances if applicable.		
	* This inspec	etion is valid for three (3) months only.		

Mississippi State Department of Health

Revised 6-90

Form No. 287